

All Purpose Display & Storage Freezer—FML50

Full height Internal
LED lighting

Dual magnet door
sealing and plastic
fascia, thermal break

Orford Softline
Door

Full Length Easy
Grip Door Handle

Easy roll lockable
castors



Self closing toughened
safety glass doors, dou-
ble low E , Argon filled,
incorporating the latest
warm edge technology

Ducted air flow system
for even temperature
distribution

Bright clean internal space
Easy wipe clean

Digital Controller

Market recognisable
"Orford" look



High Energy Efficiency

The FML freezer series have an easily removable





Orford Freezer FML-50	3 Door Vertical Display Freezer
Specifications	
Construction	Powder Coated galvanized steel Interior /Exterior White
FML-50	3 DOOR FREEZER
Capacity	1450 Litres (gross)
Dimensions	1880 w x 760 D x 2039 H (mm) (B models onwards)
Weight	305 kg (net)
Doors	3 x Self Closing, Triple Glazed Safety Glass, Argon filled with Double Heat reflective Low E,
* Energy Consumption	34.3 kWh/24h/m2
Operating Temp	-18° to -22° C.
Ambient Temp Range	32 degrees
Power Point	220 - 240v 50Hz. (1 x 15 AMP power outlet)
Common Specifications	FML20 / FML30 / FML50
Compressor	Danfoss
Thermometer	Digital Elitech Controller
Shelves per door	4 Height Adjustable Heavy Duty PVC Coated with 1 Fixed Stainless Steel Base shelves
Shelf Adjustment	12mm Increments
Condensate Disposal	Automatic by energy efficient, No Cost, Hot Gas
Footings	Heavy Duty 2.5mm Castors, Lockable Front
Interior Light	LED light
Refrigerant	R290a Natural Refrigerant (B models onwards)
Drier	Solid Core
Insulation	60mm Polyurethane, CFC, HCFC, HFC Free
Cabinet Classes	
Condenser Filter	Easy front access
Door	Orford Softline Door
Drip Tray Evaporation Method	Hot Gas
Kick Panel	Easy to unclip and remove kickpanel
Defrost	Energy Efficient Hot Gas
Compliance	MEPS, EMC,

