

All Purpose Display & Storage Freezer

Full height Internal LED lighting

Dual magnet door sealing and plastic fascia, thermal break

Orford Softline Door

Full Length Easy Grip Door Handle

Adjustable shelves

Easy roll lockable castors

Self closing toughened safety glass doors, double low E, Argon filled, incorporating the latest warm edge technology

Ducted air flow system for even temperature distribution

Bright clean internal space

Easy wipe clean

Digital controller

Market recognisable "Orford" look

The FML freezer series have an easily removable Kick panel



High Energy Efficiency





Orford Freezer FML20

Vertical Display Freezer

Specifications

Construction	Powder Coated galvanized steel Interior /Exterior White standard (black optional)
FML-20	1 DOOR FREEZER
Capacity	560 Litres (gross)
Dimensions	750 w x 760 D x 2039 H (mm) (B models onwards)
Weight	150kg (net)
Temp	-18c—-22c
Doors	1 x Self Closing, Triple Glazed Safety Glass, Argon filled with Double Heat reflective Low E,
Ambient temp	32c degrees
Weight	166 Kg (net)
Power Point	220—240v (1 x 10 AMP powerpoint)
* Energy Consumption	12.7 kWh/24h/m2

Common Specifications

FML20 / FML30 / FML50

Compressor	Danfoss
Thermometer	Digital Elitech Controller
Shelves per door	4 Height Adjustable Heavy Duty PVC Coated
Shelf Adjustment	12mm Increments
Condensate Disposal	Automatic by energy efficient, No Cost, Hot Gas
Footings	Heavy Duty 2.5mm Castors, Lockable Front
Interior Light	LED light with light switch
Refrigerant	R290a—Natural Refrigerant (B models onwards)
Drier	Solid Core to suit
Insulation	60mm Polyurethane, CFC, HCFC, HFC Free
Cabinet Classes	
Condenser Filter	Easy front access
Door	Orford Softline door
Drip Tray Evaporation Method	Hot Gas
Kick Panel	Easy to unclip and remove kick panel
Defrost	Energy Efficient Hot Gas
Compliance	MEPS compliant, EMC, Electrically compliant

