


## All Purpose Display & Storage Refrigerator—GDM650-HG-B



**Full height Internal LED lighting**

**Dual magnet door sealing and plastic fascia, thermal break**

**Orford Softline Tropicalised HEATED Door.**

**Full Length Easy Grip Door Handle**

**Natural Refrigerant R290**

**Lock and Key Standard**

**Easy roll lockable castors**

**Self closing toughened safety glass doors, double low E , Argon filled, incorporating the latest warm edge technology**

**GDM fridges pigeon pair the Orford FML freezers**

**Bright clean internal space  
Easy wipe clean**

**Electronic Controller**

**Market recognisable "Orford" look**

**The GDM fridge series have an easily removable Kick panel**

**High Energy Efficiency**





Orford Fridge GDM650 Specifications	1 Door Vertical Display Refrigerator
Construction	Powder Coated galvanized steel Interior /Exterior White
<b>GDM650-HG-B</b>	<b>1 DOOR REFRIGERATOR</b>
Capacity	635 Litres (gross)
Dimensions	750w x 710 D + 30 mm stopper x 2039 H (mm)
Weight	130 kg (net)
Doors	1 x Self Closing, Triple Glazed Heated Safety Glass, Argon filled with Double Heat reflective Low E,
Temp	1° — 5 °
Ambient Temperature	32 degrees
Power Point	1 x 10 AMP plug
* Energy Consumption	5.1 kWh/24h/m2
<b>Common Specifications</b>	<b>GDM650 / 1000 / 1600</b>
Compressor	Donper K480DU RoHS compliant
Thermometer	Digital Carel Ezy Controller
Shelves per door	5 Height Adjustable Heavy Duty PVC Coated
Shelf Adjustment	12mm Increments
Shelf size	565 mm W x 490 mm D
Footings	4 x Heavy Duty 70 mm Castors, Lockable Front
Interior Light	LED light
Refrigerant	R290a
Drier	Solid Core
Insulation	60mm Polyurethane, CFC, HCFC, HFC Free
Cabinet Classes	
Condenser Filter	Easy front access
Door	Orford Softline doors
	Lock and Key standard on all models
Condensation Management	Tropicalised Heated Glass Door
Kick Panel	Easy unclip and remove system
Defrost	Auto Defrost
Compliance	MEPS, EMC,

